

| ΥΠΟΣΥΣΤΗΜΑ | ΚΑΤΗΓΟΡΙΑ | ΑΝΑΛΥΤΙΚΗ ΠΕΡΙΓΡΑΦΗ / ΤΕΧΝΙΚΑ ΧΑΡΑΚΤΗΡΙΣΤΙΚΑ   | ΠΟΣΟΤΗΤΑ |
|------------|-----------|--|----------|
| 1          | 1         | Nemo Invex Active Chassis Kit HW configuration, including:<br>- Nemo Invex Chassis<br>- Nemo Invex 12 VDC power cable (unterminated)<br>- Nemo Invex 12 VDC cigarette lighter adapter (7 A max)<br>- Nemo Invex AC Adapter 320 Watt 115/230 VAC 50/60 Hz<br>- Nemo Invex Blank Panels (11pcs)<br>- Nemo Invex System Interface (SI) module<br>- Ethernet cable, length 3 m<br>- GPS antenna<br>- Nemo Invex Hold Down Brackets | 2        |
| 1          | 1         | Nemo Invex Passive Chassis (13 slots), including:<br>- Nemo Invex auxiliary power cable<br>- Nemo Invex Blank Panels (12pcs)<br>- Nemo Invex Chassis Brackets  | 1        |
| 1          | 1         | Nemo Invex GPS Dead Reckoning Kit. Includes all the items listed below:<br>Nemo Invex DR- Input Module, 499082-58, 1 pcs<br>Interconnect cable WN000037 1 pcs<br>DR Cable Kit (Includes speed sensor wire 2Cond 20AWG 1 pcs and backlight wire 2Cond 20AWG 1 pcs, Length 15ft, Connector Tap 22-16 AWG RED, 4 pcs, Connector Ring 16-22 AWG RED, 4 pcs)  | 1        |
| 1          | 1         | Nemo Invex RF Splitter 1:4 for Nemo Invex, NemoRFSplit-4   | 7        |
| 1          | 1         | Nemo Invex UIC-200 Module<br>UIC-200 module with Intel Core i7-processor provides support for the higher data rates required with LTE UEs:<br>- Supports dual LTE UE multi-data testing simultaneously<br>- Enables a maximum of up to 200Mbps data rates (100Mbps/UE)<br>- With one Nemo Invex active chassis and seven UIC-200 modules, it is possible to benchmark up to 14 LTE UEs simultaneously.                         | 8        |
| 1          | 1         | Nemo Invex, Handset Isolation Module with Samsung Galaxy S4 GT-i9505 Terminal with external antenna<br>LTE 800/900/ 850/ 1800/ 2100/ 2600 (E-UTRA bands 20, 5,8, 3, 1 and 7)<br>WCDMA/ HSPA+ DC 850 / 900 / 1900 / 2100<br>GSM/ EDGE 850 / 900 / 1800 / 1900   | 6        |

|   |   |   |   |
|---|---|---|---|
|   |   | <p>Nemo Invex Handset Isolation Module with external SIM Access;<br/> External SIM front assembly<br/> Samsung Galaxy SIII SIM adapter<br/> Invex HIM Battery eliminator, Samsung Galaxy S4<br/> Invex Power Cable<br/> Invex HIM Audio Cable, Samsung Galaxy S4<br/> Invex HIM Data Cable Samsung Galaxy S4<br/> 2 x Invex RF Cable Samsung Galaxy S4<br/> 2 x Mag. Antenna MGRM-UMB-1C (750-1250 MHz &amp; 1650-2700 MHz)</p>       |   |
| 1 | 1 | <p>Nemo Invex USB Isolation Module with Huawei E392u-12 LTE USB modem<br/> LTE UE cat. 3 (102Mbps/ 51Mbps)<br/> Nemo Invex USB Modem Isolation Module<br/> 2 x Isolation module RF antenna cable, Huawei<br/> Isolation module USB cable, length 18 inches<br/> Antenna (2 pcs)</p>   | 6 |
| 1 | 1 | <p>Nemo FSR1 Scanner Receiver GWIRBASEN (412054-00).</p>  | 2 |
| 1 | 1 | <p>Nemo FSR1 Scanner RF Front End (412054-06)<br/> Frequency Ranges:<br/> 925 – 960 MHz (GSM 900 DL, WCDMA 900 DL,<br/> LTE 900 DL, E-UTRA band 8)<br/> 1805 – 1880 MHz (GSM 1800 DL, WCDMA 1800 DL, LTE 1800 DL, E-UTRA band 3)<br/> 2110 – 2170 MHz (WCDMA 2100 DL, WCDMA 2100AWS DL,<br/> LTE 2100, LTE 2100AWS, E-UTRA bands 1, 4)<br/> 2500- 2690MHz (LTE FDD 2600 DL/ UL, E-UTRA band 7,<br/> LTE TDD 2600, E-UTRA band 38)</p> | 2 |
| 1 | 1 | <p>Nemo FSR1 Scanner RF Front End (412054-08)<br/> Frequency Ranges:<br/> 791 – 821 MHz (LTE FDD 800, E -UTRA band 20)<br/> 1900 – 1920 MHz (LTE TDD 1900, E -UTRA band 33)<br/> 2300 – 2400 MHz (LTE TDD 2300, E -UTRA band 40)<br/> 2496 – 2690 MHz (LTE FDD 2600, E-UTRA band 7, LTE TDD 2600, E -UTRA bands 38, 41)<br/> Including:<br/> Scanner antenna 1 pcs, MGRM-WLF-1C10<br/> 694- 894MHz &amp; 1700- 2700MHz</p>            | 2 |

|   |   |  |   |
|---|---|--|---|
|   |   | GW4AAM0725 (421010-05)   |   |
| 1 | 1 | Nemo FSR1 Scanner Option GSM 850/ 900/ 1800/ 1900 MHz  | 2 |
| 1 | 1 | Nemo FSR1 Scanner WCDMA 850/ 900/ 1900/ 2100/ 2100 AWS   | 2 |
| 1 | 1 | Nemo FSR1 Scanner LTE FDD bands 700, E800, 850, 900, 1800, 1900, 2100, 2100 AWS and 2600 (E -UTRA bands 1 -5, 7, 8, 12, 13, 14, 17, 19, 20, 25)  | 2 |
| 1 | 1 | Nemo Invex Pro Installation Accessory Kit (EU) - for car installations, including:<br>1 x Power GatePOWER-GATE™ Solid-State Devices Uni-Directional Relay RB150"<br>2 x Cole Hersee 24213-200A Solenoid<br>1 x Bussman CB185-120 Circuit Breaker<br>1 x Scosche CoreblockM4 Maxi Fuse Dist. Block<br>2 x Maxi Fuse 30A (Orange)<br>1 x High Temp Spiral Wrap 7.5m (25')<br>1 x Mounting brackets for spiral wrap and screws, 10 pack<br>2 x Red Power Cable 5.19mm (AWG4) 6m (20')<br>2 x Black Power Cable 5.19mm (AWG4) 6m (20')<br>10 x Tin plated 4GA 3/8 copper terminals 20 pk<br>1 x T1 Red Battery Feeder Stud 46211-R 3/8 x 16 5/8"<br>1 x T2 Black Battery Feeder Stud 46211-01 3/8 x 16 5/8"<br>4 x Switch to starter cable 5.19mm (AWG4) 0.4m (16"), Red<br>1 x Switch to starter cable 5.19mm (AWG4) 0.4m (16"), Black<br>1 x StreetWires DBX3448 Dist Block 4 AWG In To Four 8 AWG Out<br>1 x TOP POST 4GA. FITS 3/8" STUD, NO LEAD, 0.64m (25") RED<br>1 x TOP POST 4GA. FITS 3/8" STUD, NO LEAD, 0.64m (25") Black<br>1 x Flat Cable 3/16 3 conductor for switch 7.5m (25')#768570<br>10 x Cable Ties Black length 196mm (7.7")<br>1 x S3 Main Switch. SPST On-Off LED Illuminated Round Rocker<br>1 x S4 Aux. Switch. SPST On-Off LED Illuminated Round Rocker, Green<br>1 x JEGS Stainless Steel Battery Tray Kit<br>20 x Hex head sheet metal screws DIN 7976/ 7504-K (Würth) | 1 |

|   |       |  |   |
|---|-------|--|---|
|   |       | <p>1 x Crimp tool 12-4 gauge hex die. LUG-12-4-HD</p> <p>1 x Heavy Duty Cable Stripper</p> <p>1 x Split Loom Installation Tool</p> <p>1 x Installation Instructions</p> <p>1 x Inverter Mascot 12V 2286 (1000W)</p> <p>1 x Battery VARTA 12V 85Ah</p>  |   |
| 1 | 2     | <p>Nemo Walker Backpack carry on solution</p> <p>1 x Nemo Walker Backpack with required accessories</p> <p>Holds up to six terminals</p> <p>Includes:</p> <p>Nemo Walker Backpack (NW420000-10)</p> <p>Mechanics (NW422000-10)</p> <p>cabling</p> <p>Built in battery-pack</p>   | 1 |
| 1 | 2     | <p>Samsung Galaxy S4 GT-i9505 measurement handset with external antenna</p> <p>LTE 800/900/ 850/ 1800/ 2100/ 2600 (E-UTRA bands 20, 5,8, 3, 1 and 7)</p> <p>WCDMA/ HSPA+ DC 850 / 900 / 1900 / 2100</p> <p>GSM/ EDGE 850 / 900 / 1800 / 1900</p> <p>2 x RF Cable Samsung Galaxy S4</p> <p>2 x Mag. Antenna MGRM-UMB-1C (750-1250 MHz &amp; 1650-2700 MHz)</p>  | 6 |
| 1 | 1     | <p>Nemo Audio Server Dell PowerEdge T110_2</p> <p>Supports POLQA and PESQ measurements for up to 12 lines simultaneously</p> <p>The package includes:</p> <p>English Docs with Euro Power Cord</p> <p>PE T110-2 Server Tower Chassis</p> <p>FP/BL - Euro - 17in Black Flat Panel</p> <p>Dell Black 2 Button USB Scroll Optical Mouse</p> <p>US/Euro (QWERTY) Quietkey USB Black Keyboard</p> <p>PE T110 Electronic System Documentation and OpenManage DVD</p> <p>C1 Cabled MST No Raid with On-board SATA Controller, Min. 1 Max. 4 SATA Only</p> <p>1Yr Basic Warranty</p> <p>Preinstalled NSM (Nemo Server Manager) application</p> <p>Nemo Server Image</p> <p>1 x Data Cable 5E S-FTP 5m (420040-00)</p> <p>Nemo Server USB Copy Protection Key (499003-00)</p> | 1 |
| 1 | 1     | <p>30 x ISDN Lines OpenPR1e ISDN V3 Card for VQ Server, 30 lines T110-2 (499016-08).</p> <p>Max 1pcs per server.</p>   | 1 |
| 1 | 1 & 2 | <p>Nemo Data Server Dell PE T110-2 XEON, [4 port Network card (IP addresses)]</p>  | 1 |

|       |             |  |   |
|-------|-------------|--|---|
|       |             | <p>PowerEdge T110 II Tower Chassis, Up to 4x 3.5" Cabled HDDs</p> <p>Intel Xeon E3-1270v2 Processor (3.5GHz, 4C/8T, 8M Cache, 69W, Turbo)</p> <p>1 2GB Memory (1x2GB Single Rank UDIMM) 1600MHz</p> <p>1 500GB, SATA, 3.5-in, 7.2K RPM Hard Drive (Cabled)</p> <p>1 16X DVD+/-RW ROM Drive SATA with SATA Cable</p> <p>1 European 220V Spare Power Cord</p> <p>1 Embedded BMC</p> <p>1 Dell MS111 USB Optical Mouse</p> <p>1 Keyboard : US/Euro (QWERTY) Dell KB212-B WinServer 2012 QuietKey USB Keyboard Black</p> <p>1 C1 4HD - No RAID with On-board SATA Controller, Min. 1 Max. 4 SATA Drives</p> <p>1Yr Basic Warranty</p> <p>Preinstalled NSM (Nemo Server Manager) application</p> <p>Nemo Server Image</p> <p>1 x Data Cable 5E S-FTP 5m (420040-00)</p> <p>Nemo Server USB Copy Protection Key (499003-00)</p> <p>1 x Intel PRO/1000 PT Quad Port Server Adapter PCI Express Card EXPI9404PTBLK (499047-00)</p> <p>4 x Data Cable 5E S-FTP 5m (420040-00)</p> |   |
| 1 & 2 | 1 & 2 (YΣ1) | <p>Analyze Server HW DELL PowerEdge T620 Tower -Server HW, including:</p> <p>2 x Intel Xeon E5-2667 2.90GHz, 15M Cache, 8.0GT/s QPI, Turbo, 6C, 130W, DDR3-1600MHz</p> <p>1 x Chassis with up to 16, 2.5" Hard Drives, Tower Configuration</p> <p>1 x 1333 MHz RDIMMs</p> <p>4 x 8GB RDIMM, 1333 MHz, Low Volt, Dual Rank, x4</p> <p>2 x Heat Sink for T620 with 1, 150W (or Greater) Processor</p> <p>3 x 1TB, SATA, 2.5-in, 7.2K RPM Hard Drive (Hot-plug)</p> <p>1 x DVD+/-RW, SATA, Internal</p> <p>1 x Dual, Hot-plug, Redundant Power Supply (1+1), 750W</p> <p>2 x European Spare Power Cord 220V</p> <p>2 x Broadcom 5720 DP 1Gb Network Interface Card</p> <p>1 x 8 Pin Phone Connector, Back Cover</p>   | 1 |

|       |   |   |    |
|-------|---|---|----|
|       |   | <p>1 x Dell MS111 USB Optical Mouse<br/> 1 x Keyboard : UK/Irish (QWERTY) Dell KB212-B QuietKey USB Keyboard Black<br/> 1 x iDRAC7 Express</p> <p>Software<br/> 1 x Windows Server 2008 R2 SP1, Standard Edition, English, Incl. 5 CALs, No Media<br/> 1 x Windows Server 2008 SP2 Media, Standard Edition, 32 and 64 Bit, English<br/> 1 x DVD Media for Windows Server 2008 R2 SP1, Standard Edition, English</p>   |    |
| 2     | - | <p>Nemo Handy-A LTE Autonomous with Samsung Galaxy S4 GT-i9505 with RF container and Aluminum box Includes all needed sw and terminal.<br/> Terminal specifications:<br/> LTE 800/ 850/ 1800/ 2100/ 2600 (E-UTRA bands 20, 5, 3, 1 and 7)<br/> WCDMA/ HSPA+ DC 850 / 900 / 1900 / 2100<br/> GSM/ EDGE 850 / 900 / 1800 / 1900</p>   | 60 |
| 2     | - | <p>Κέλυφος για την τοποθέτηση τριών Nemo Handy-Autonomous, περιλαμβάνει UPS, 2 x RF-splitters, 2 x Mag. Antenna MGRM-UMB-1C (750-1250 MHz &amp; 1650-2700 MHz)</p>  | 20 |
| 1     | 2 | Lenovo Tablet PC  | 1  |
| 1     | 1 | Lenovo Notebook   | 2  |
| 1 & 2 | 1 | Dell Notebook   | 1  |
| 1     | 1 | <p>Skoda Superb Combi 1.8TSI 160hp 4WD, έκδοση Elegance, με σχάρα οροφής και ειδική κατασκευή για το κεραιοσύστημα Μεταλ.χρωμα(Ασημι)<br/> Συναγερμος<br/> Συστημα πλοηγησης Columbus<br/> Sunset(Φιμε κρυσταλλα)<br/> Διαχωριστικο πλεγμα χωρου αποσκευων<br/> Μεταβαλλόμενος χώρος αποσκευών, συρόμενος με ενσωματωμένα άγκιστρα<br/> Καλυμμα χωρου αποσκευων με διχτυ<br/> Διχτυα χωρου αποσκευων<br/> Ενισχυμενο δυναμο 380A 72Ah<br/> Τελη κυκλοφοριας και εξοδα μεταβιβασης</p> | 1  |